

STYLE 304

ALL STAINLESS STEEL SERVICE SADDLES



MATERIAL SPECIFICATIONS

SHELLS: Stainless steel per ASTM A240, type 304, passivated for corrosion resistance.

BOLTS: UNC rolled thread, 304 stainless steel.

NUTS: Stainless steel per ASTM A194, type 304.

WASHERS: Stainless steel type 304 and plastic lubricating washers.

GASKET: NBR per ASTM D2000 MBC 610, compounded for water and sewer service. Other compounds available on request.

TAPPED OUTLET: Stainless steel per ASTM A240, type 304.



MEETS
AWWA C800

304 SINGLE BOLT (not recommended for A/C pipe)						
NOM. PIPE SIZE	O.D. PIPE RANGE	LENGTH	BOLT SIZE	TAP		APPROX. WEIGHT EA. (lbs.)
				I.P. 1/2" - 1"	C.C. 3/4" OR 1"	
2"	2.13 2.38	4"	1/2"	\$140.91	\$140.91	2 #
2 1/2"	2.63 - 2.88	4"	1/2"	144.72	144.72	2 #
3"	3.00 - 3.25 3.25 - 3.50 3.50 - 3.75 3.75 - 4.00	4"	1/2"	147.55	147.55	2 #
4"	4.00 - 4.30 4.50 - 4.80 4.80 - 5.20	4"	1/2"	172.66	172.66	3 #
5"	5.20 - 5.60 5.60 - 6.00	4"	1/2"	174.83	174.83	3 #
6"	6.00 - 6.40 6.50 - 6.90 6.90 - 7.30	4"	5/8"	237.85	237.85	4 #
8"	8.00 - 8.40 8.63 - 9.05 9.05 - 9.45	4"	5/8"	240.89	240.89	5 #

For easiest installation, choose the saddle with your pipe O.D. closest to the bottom of the range.

Other O.D.s available P.O.A.

TO ORDER: Use upper range when ordering. Add tap size. Be specific when ordering.

Tapped outlet products are NO CANCEL/NO RETURN items.

EXAMPLE: 304 - 4.80 x 3/4" I.P.