



STYLE SS2 (TWO SECTION) WIDER RANGE .80"

MATERIAL SPECIFICATIONS

- SHELLS AND LUGS:** Stainless steel per ASTM A240, type 304.
- BOLTS:** UNC rolled thread, type 304 stainless steel.
- NUTS:** Stainless steel per ASTM A194, type 304. Coated to prevent galling.
- WASHERS:** Stainless steel, type 304 and plastic lubricating washers.
- GASKETS:** SBR per ASTM D2000 MAA 610. Compounded for water and sewer service. Other compounds available on request.



SS2-7.64 x 10" REPAIR CLAMP



NSF61 certified upon request.

**MEETS
AWWA C230**

Certified to
NSF/ANSI 61 & 372

REPAIR CLAMPS

NOM. PIPE SIZE	O.D. RANGE (inches)	CATALOG NUMBER	LENGTH / WEIGHT						
			8"	10"	12"	16"	20"	24"	30"
4"	4.47 - 5.27	SS2 - 5.27 x length SS2 - 5.57 x length SS2 - 6.00 x length ¹	\$401.58	\$527.46	\$624.61	\$746.74	\$1,000.00	\$1,278.95	N/A
	4.77 - 5.57		9#	12#	13#	17#	25#	30#	
	5.20 - 6.00								
6"	6.57 - 7.37	SS2 - 7.37 x length SS2 - 7.64 x length SS2 - 8.00 x length ¹	461.64	593.91	676.47	873.41	1,192.21	1,567.50	1,687.43
	6.84 - 7.64		11#	15#	17#	22#	28#	34#	43#
	7.20 - 8.00								
8"	8.59 - 9.39	SS2 - 9.39 x length SS2 - 9.79 x length SS2-10.00 x length ¹	528.39	659.41	768.53	1,000.00	1,353.76	1,790.34	1,903.29
	8.99 - 9.79		12#	17#	19#	24#	30#	36#	47#
	9.20 - 10.00								
10"	10.70 - 11.50	SS2-11.50 x length SS2-11.84 x length SS2-12.20 x length	534.20	864.67	1,186.80	1,244.54	1,659.42	2,206.06	2,486.51
	11.04 - 11.84		15#	18#	23#	32#	41#	47#	59#
	11.40 - 12.20								
12"	12.70 - 13.50	SS2-13.50 x length SS2-13.95 x length SS2-14.30 x length SS2-14.51 x length	684.65	991.29	1,347.42	1,423.61	1,921.44	2,450.73	2,800.18
	13.15 - 13.95		16#	19#	25#	33#	41#	50#	61#
	13.50 - 14.30								
14"	15.00 - 15.80	SS2-15.80 x length SS2-16.75 x length	981.57	1,325.52	1,712.44	1,908.76	2,584.60	3,057.52	3,219.18
	15.95 - 16.75		18#	21#	27#	33#	43#	50#	64#

¹ Recommended for use on CL200 ACRB

NUMBER OF BOLTS PER CLAMP LENGTH

O.D. RANGE	8"	10"	12"	16"	20"	24"	30"
4.47 - 9.99	4	6	6	8	10	12	16
10.00 - 16.75	6	6	8	10	14	16	20

FOR TAPPED SS2 SEE PAGE 2-14.

FOR SEWER O.D.S SEE PAGE 7-8.

For higher working pressures, clamp length should equal or exceed diameter of pipe. Some sizes and lengths not listed are available on request. Clamps are not to be used for joining plain end pipe.

TO ORDER: Specify catalog number x length of clamp desired.

EXAMPLE: For a two-section clamp for pipe with an O.D. between 6.84 and 7.64 and clamp length of 10", order **SS2 - 7.64 x 10"**